

TB-X08 Termination Box

Features

- ✓ Compact design (260 x 195 x 63.5 mm)
- ✓ Free breathing box for indoor use
- ✓ In-line and butt configuration possible for main cable
- ✓ Wrap around cable seals for main cable and drops
- ✓ Not required to cut loop-through fibers from riser cable
- ✓ Window cuts as small as 70 mm possible with certain cable constructions
- ✓ Compatible with mechanical splice, and heat shrink protective sleeves
- ✓ LSZH material
- ✓ Transient free customer provisioning
- ✓ Drop cables are terminated individually
- ✓ Separate storage of un-connected fibers from spliced drop fibers
- ✓ Possibility to integrate PON splitters
- ✓ Main cable up to 15 mm diameter, Drop cable up to 3 mm diameter
- ✓ Easy drop cable termination on strain relief device



TB-X08A

Application

Wall Mounting and Pole Mounting



TB-X08B

Specifications & Ordering Information

Order No	Dimensions LxWxH(mm)	Cable Ports	Spliced Fiber Storage Capacity	PLC Splitter	Adaptor Capacity
ALF-TB-X08A	260x195x63.5	2 cable ports (for cables with max diameter 15 mm)	12 Splices	1x8, 1x16 PLC Splitter	8 SC Simplex Adaptors
ALF-TB-X08B		16 drop cable ports (for Dropcable up to 3 mm diameter)	24 Splices	Not available	


TB-X12 Termination Box

Features

- ✓ Up to 12 drop cables
- ✓ Up to 12 Simplex SC adaptors
- ✓ Can accommodate 1 x 8, 1 x 4 PLC Splitter
- ✓ Maximum capacity is 24F
- ✓ 2 main ports is for 1 loop cable or 2 cables with max Ø 12 mm.
- ✓ The reserved port is for cables with max Ø 12mm
- ✓ The 12 small ports, each port can hold 1 drop cable
- ✓ Bending radius > 30mm
- ✓ Outdoor use(IP 65)
- ✓ Designed for Wall and Pole mount applications
- ✓ Safety lock
- ✓ Rugged and durable construction for long term reliability (UV resistance)
- ✓ Design for small and medium volumes of fiber optic cables
- ✓ Re-usable
- ✓ ROHS compliance



TB-X12A (with rubber seal)



TB-X12B (with cable gland)

Specifications & Ordering Information

Order No	Dimensions LxWxH(mm)	Cable Ports	Spliced Fiber Storage Capacity	PLC Splitter	Adaptor Capacity
ALF-TB-X12A	258x207x64	2 rubber ports: each port for 1 cable with max 12 mm 1 reserved port for 1 cable with max 12 mm	24 Splices	1x4, 1x8 PLC Splitter	12 SC Simplex or 12 LC Duplex Adaptors
ALF-TB-X12B		2 cable gland: each port for 1 cable with max 12 mm 1 reserved port for 1 cable with max 12 mm			

